

Deskstar™ 7K1000.C

3.5-INCH HARD DISK DRIVES

HITACHI
Inspire the Next

Energy-efficient storage for power-friendly PCs

Highlights

- > Capacities up to 1TB¹
- > 7200 RPM performance
- > Up to 18% idle power savings over previous generation product
- > Halogen-free design for eco-friendly footprint
- > Built on award-winning proven design

Applications

- > Consumer and commercial computers
- > Personal storage
- > PC gaming

Features and Benefits

	Feature / Function	Benefits
Power	Advanced Power Management	Reduces power during idle periods
	HIVERT™ technology	Best-of-breed power consumption
Capacity	160GB to 1TB	Full range of capacity points
Reliability	Thermal Fly-height Control (TFC)	Better soft error rate for improved reliability and performance
	Head load/unload	Protects disk during non-operation
	ECC and CRC protection	Data integrity enhanced throughout circuits
	SMART command transport	Adaptive error correction
	Internal thermal sensor	Improves data integrity
Performance	Up to 32MB cache buffer	Faster data processing



1TB, 750, 640, 500, 320,
250 and 160GB
7200 RPM | SATA 3Gb/s



Less power, more performance

The Deskstar™ 7K1000.C hard drive is a 7200 RPM 3.5-inch hard drive that provides an exceptional blend of power efficiency and performance, making it an ideal solution for power-friendly consumer and commercial desktop computers. This third-generation 1TB hard drive from Hitachi boosts media transfer rate performance by as much as 13% over its predecessor. Leveraging eighth-generation power management technology, as well as power-saving HIVERT™ innovations pioneered on the popular 2.5-inch line of notebook hard drives from Hitachi, this new desktop drive provides up to 18% idle power savings over the previous model, delivering best-in-class power management and thermal emissions.

Innovation for a more sustainable environment

The Deskstar 7K1000.C demonstrates Hitachi's ecological leadership with its halogen-free design and power-efficient operation. Both these features helped qualify the drive for the Hitachi EcoTrac classification, which identifies products that minimize environmental impact in the areas of product design, manufacturing, operation and disposal.

Power efficiency supports ENERGY STAR™ 5.0

The ENERGY STAR 5.0 specifications released by the U.S. Environmental Protection Agency (EPA) are recognized around the world as a way of identifying energy-efficient PCs and other computer equipment. PCs that meet the ENERGY STAR 5.0 criteria are expected to become increasingly popular with both corporations and consumers. Some corporations are choosing to purchase ENERGY STAR PCs as part of their "green" initiatives. The low power profile of the Deskstar 7K1000.C hard drive enables a reduction in overall system power requirements, which helps PC manufacturers achieve ENERGY STAR ratings.

Specifications

Model(s)	HDS721010CLA332 HDS721075CLA332 HDS721064CLA332 HDS721050CLA362 HDS721032CLA362 HDS721025CLA382 HDS721016CLA382
Configuration	
Interface	SATA 3Gb/s
Capacity (GB) ¹	1TB / 750 / 640 / 500 / 320 / 250 / 160
Max. areal density (Gbits/sq. in.)	352
Performance	
Data buffer (MB) ²	32 / 32 / 32 / 16 / 16 / 8 / 8
Rotational speed (RPM)	7200
Media transfer rate (Mbits/s, max)	1589
Interface transfer rate (MB/s, max)	300
Reliability	
Error rate (non-recoverable, bits read)	1 in 10 ¹⁴
Load/unload cycles (at 40° C)	300,000
Availability ³ (hrs/day x days/wk)	24x7
Acoustics	
Idle (Bels, typical)	1TB / 750GB / 640GB 500GB / 320GB / 250GB / 160GB
	2.4 2.5
Power	
Requirement	+5 VDC (+/-5%) +12 VDC (+/-10%)
Startup current (A, max.)	1.5 (+5V), 2.0 (+12V)
Idle (W)	1TB / 750GB / 640GB 500GB / 320GB / 250GB / 160GB
	4.4 3.6
Physical size	
z-height (mm)	26.1
Dimensions (width x depth, mm)	101.6 (+/-0.25) x 147
Weight (typical, g, max.)	1TB / 750GB / 640GB 500GB / 320GB / 250GB / 160GB
	680 400
Environmental (operating)	
Ambient temperature	0° to 60° C
Relative humidity (non-condensing)	8% to 90%
Shock (half-sine wave)	70
Vibration, random (G RMS 5 to 500 Hz)	0.67 (XYZ)
Environmental (non-operating)	
Ambient temperature	-40° to 70° C
Relative humidity (non-condensing)	5% to 95%
Shock (half-sine wave, G (2ms))	350
Vibration, random (G RMS 2 to 200 Hz)	1.04 (XYZ)

Hitachi Global Storage Technologies trademarks are intended and authorized for use only in countries and jurisdictions in which Hitachi Global Storage Technologies has obtained the rights to use, market and advertise the brand. Contact Hitachi Global Storage Technologies for additional information. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to Hitachi Global Storage Technologies' products, programs or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hitachigst.com/support, for additional information on product specifications. Photographs may show design models.

Hitachi quality and service

All Hitachi hard drives are designed to the highest quality standards with field-proven components. They are backed by Hitachi's worldwide technical support and integration services, enabling customers around the globe to bring their products to market quickly.

How to read the Deskstar model number

HDS721010CLA332 = 1TB, 32MB buffer

H = Hitachi

D = Deskstar

S = Standard model

72 = 7200 RPM

10 = Full capacity – 1TB

10 = Capacity this model, 10 = 1TB

(75 = 750GB, 64 = 640GB, 50 = 500GB,
32 = 320GB, 25 = 250GB, 16 = 160GB)

C = Generation code

L = 26.1mm z-height

A3 = Interface, SATA 3Gb/s

3 = 32MB buffer (6 = 16MB, 8 = 8MB)

2 = Reserved

Information and Technical Support

www.hitachigst.com (Main Web site)

www.hitachigst.com/partners (Partner Web site)

North America

support_usa@hitachigst.com

Toll free: 1 888 426-5214, Direct: 1 507 322-2370

Asia Pacific

support_ap@hitachigst.com / 65 6840 9595

EMEA and UK

support_uk@hitachigst.com / 44 20 7133 0032

Germany

support_uk@hitachigst.com / 49 6929 993601

Program Support

Partners First™ Program

channelpartners@hitachigst.com

¹ One GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes) when referring to hard drive capacity. Accessible capacity may be less.

² Portion of buffer capacity used for drive firmware

³ Intended for low duty cycle, non mission-critical applications in PC, nearline, and consumer electronics environments, which may vary from application to application. Note that customer environments may vary from application to application.

© 2009 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
3403 Yerba Buena Road
San Jose, CA 95135 USA

Produced in the United States 8/09. Revised 9/09.
All rights reserved.

Deskstar™, HIVER™ and Partners First™ are trademarks of Hitachi Global Storage Technologies. ENERGY STAR® is a registered mark of the United States Environmental Protection Agency.

The EcoTrac symbol identifies Hitachi hard drives that deliver on the principles of lower operating costs, safer product disposal and a more sustainable environment.

 Hitachi Global Storage Technologies